


FI SERIES

.049" (1.25mm) WIRE TO BOARD CONNECTOR



Specifications

Current rating: 1A AC,DC

Voltage rating: 50V AC,DC

Temperature range: -25°C to +85°C
(including temperature rise)


Contact resistance: Initial value/20 mΩ Max.

After environmental testing/20mΩ Max.

Insulation resistance: 100MΩ MIN.

Withstanding voltage: 500V AC/minute

Applicable wire: AWG#28-32




Assembly layout

F001H .049" (1.25mm) SERIES HOUSING

Features:

unit:mm

- * MAT'L: NYLON 66 UL94V-0
- * MATES WITH: FI-T SERIES TERMINAL





| PART NO. | A | B |
|----------|------|-------|
| F001H 20 | 28.5 | 23.75 |
| F001H 30 | 41.0 | 36.25 |

F001 .049" (1.25mm) SERIES TERMINAL

Features:

unit:mm

- * THICKNESS: 0.15mm
- * MAT'L: PHOSPHOR BRONZE TIN PLATED
- * MATES WITH: FI-H SERIES HOUSING



| PART NO. | WIRE RANGE | INSULATION O.D. | MATERIAL | FINISH | QTY/REEL |
|----------|------------|-----------------|-----------------|-------------|----------|
| F001T | AWG#28-32 | 0.9mm MAX | phosphor bronze | Gold plated | 15,000 |


F001PS .049" (1.25mm) SERIES WAFER

Features:

unit:mm

- * MAT'L: BODY: LCP UL94V-0
PIN: PHOSPHOR BRONZE TIN PLATED
- * MATES WITH: FI-H SERIES HOUSING

| PART NO. | A | B |
|-----------|-------|-------|
| F001PS 20 | 28.95 | 23.75 |
| F001PS 30 | 41.45 | 36.25 |



P.C LAYOUT